

AM/FM Stereo Tuner

The TU-1510AE is an AM/FM stereo tuner featuring highly sensitive reception performance and detailed, clear sound even in crowded urban areas.





Premium Silver



Black

RDS RadioTEXT

## **Features**

tion you want.

- Design matching Integrated Amplifier for the new 10AE series
  The TU-1510AE sports an external design that harmonizes well
  as a system upgrade for Denon's latest AE series of Hi-Fi audio
  components. The TU-1510AE comes in a choice of two colours,
  premium silver and black, and together with its aluminium panel of
  rich texture this tuner achieves a tasteful ambience that enhances
  the total design balance of the AE Hi-Fi audio system
- Rotary knob, for easy tuning and preset operation
   The TU-1510AE's rotary knob makes tuning and operating presets a breeze. Simply turn it to the left or right to access the sta-
- Easy-to-read dot matrix and 2-line FL display

The TU-1510AE features a large dot matrix display panel with vastly improved visual recognition characteristics. Alphanumerics are displayed more smoothly, allowing users to read the information more quickly.

• Low-impedance output circuit for high quality sound

The output circuit in the TU-1510AE has an impedance of less than 300 ohms to enable greater density in signal transmission to the amp for superior attenuation characteristics in the high-frequency range and a highly transparent sound quality.

- Easy-to-use, dedicated remote control unit
  - The TU-1510AE comes with its own remote controller that lets you conveniently perform operations such as adjusting reception frequencies up or down, flicking through preset channels, and switching bands.
- Preset memory for a total of 100 FM/AM stations, and Auto preset memory for automatically scanning and storing stations that can be received
- Up to 8 alphanumerics can be stored for displaying station call letters, nick-names, or other information.

Main Specifications	
FM section	
Tuning frequency	87.50 MHz - 108.00 MHz
Usable sensitivity	1.0μV (11.2dBf) / 1.2μV (IHF)
Signal-to-noise ratio	Mono: 77 dB (IHF), 73 dB (DIN) Stereo: 72 dB (IHF), 68 dB (DIN)
Total Harmonic Distortion	Mono: 0.15 % Stereo: 0.3 %
Frequency response	20 Hz - 15 kHz (-1.0, +0.5dB)
Stereo separation 1 kHz	43 dB
AM section	
Tuning frequency range Usable sensitivity Signal-to-noise ratio	522 kHz - 1611 kHz 18 μV 53 dB
General	
Power supply Power consumption Dimensions (W x H x D) Weight	AC 230 V, 50 Hz 10 W 434 x 73 x 286 mm 3.6 kg

Ports		
Out	RCA analog	x 1
Others	FM tuner antenna	x 1
	AM tuner antenna	x 1
	Inlet type AC-Code	yes

<sup>\*</sup> Design and specifications are subject to change without notice.

Denon is a trademark or registered trademark of D8M Holdings, Inc.