

**HTS**



HOME THEATRE SYSTEMS

**TANNOY®**

## TANNOY PERFORMANCE, DESIGNER STYLE

Tannoy HTS is a new breed of loudspeaker offering superb sound and sumptuous, design. With the power and performance to thrill with movies the HTS range integrates Tannoy's high-tech neodymium drivers and WideBand™ tweeter technology in real wood cabinets for a supremely rich and detailed sound. Slim, sleek and unobtrusive each HTS speaker is finished in a luxurious deep gloss black to match today's electronics and blend effortlessly with contemporary décor.



## HTS HOME THEATRE SYSTEMS

The HTS range is available in two simple packages. The HTS101 is a discreet, exceptionally compact wall or shelf mount system ideal for smaller spaces. The four satellites utilise a 75mm (3") mid bass driver and a 19mm (3/4") Tannoy WideBand™ tweeter with titanium dome and powerful neodymium magnet system. Housed in rigid wooden cabinets the HTS Satellites integrate seamlessly with the twin mid bass driver HTS Centre channel speaker. The HTS active subwoofer completes the HTS101 package with its 200mm (8") driver and compact cabinet capable of delivering deep bass in any room location.

The potent HTS201 is designed for larger rooms and is ideal for those looking for the best performance for music and movies. This system delivers a larger scale sound and fuller acoustic across the front soundstage with its visually striking HTS Tower speakers. Used as the main front left and right channels, the HTS Towers incorporate twin 75mm (3") mid bass drivers and the 19mm (3/4") HTS tweeter in a larger cabinet to deliver extra punch and dynamic attack. Combined with a pair of HTS Satellites for rear effects, an HTS Centre and the potent HTS Subwoofer, the HTS 201 system delivers a new level of performance and style.





## CENTRE & SATELLITES

### PERFORMANCE

<b>Recommended amplifier power</b>	25 – 100 Watts (RMS)
<b>Maximum Sensitivity (2.83Volts @ 1m)</b>	87dB
<b>Nominal impedance</b>	8 Ohms
<b>Frequency response (-6dB)</b>	100Hz – 40kHz
<b>Satellite Drivers</b>	HF: 19mm (3/4") titanium WideBand™ dome, with neodymium magnet system LF: 75mm (3") paper cone
<b>Centre Drivers</b>	HF: 19mm (3/4") titanium WideBand™ dome, with neodymium magnet system LF: 2 x 75mm (3") paper cone
<b>Crossover frequency</b>	3kHz (LF to HF)
<b>Magnetic shielding</b>	Yes
<b>Satellite Weight</b>	1.4kg (3.1lbs)
<b>Satellite Dimensions H x W x D</b>	160mm x 106mm x 142mm (6.3" x 4.2" x 5.6")
<b>Centre Weight</b>	2.3kg (5.1lbs)
<b>Centre Dimensions H x W x D</b>	106mm x 250mm x 166mm (4.2" x 9.8" x 6.6")
<b>Finish</b>	Gloss Black
<b>Supplied accessories</b>	Wall bracket, self adhesive feet

## TOWER

### PERFORMANCE

<b>Recommended amplifier power</b>	25 – 100 Watts (RMS)
<b>Maximum Sensitivity (2.83Volts @ 1m)</b>	88dB
<b>Nominal impedance</b>	6 Ohms
<b>Frequency response (-6dB)</b>	80Hz – 40kHz
<b>Drivers</b>	HF: 19mm (3/4") titanium WideBand™ dome, with neodymium magnet system LF: 2 x 75mm (3") paper cone
<b>Crossover frequency</b>	3kHz
<b>Magnetic shielding</b>	Yes
<b>Weight</b>	6.2kg (13.7lbs)
<b>Dimensions H x W x D</b>	904mm x 106mm x 167mm (35.6" x 4.2" x 6.6")
<b>Finish</b>	Gloss Black
<b>Supplied accessories</b>	Floor coupling spikes with floor protective cups, self adhesive feet

## SUBWOOFER

### PERFORMANCE

<b>Power Output</b>	100 Watts
<b>Frequency Response (-6dB)</b>	29Hz – 200Hz
<b>Crossover Frequency</b>	50Hz – 200Hz, variable control
<b>Driver</b>	200mm (8") paper cone, long throw
<b>Inputs</b>	LFE / Line Input (RCA / phono), or Left & Right speaker level inputs
<b>Power Requirements</b>	115 or 230V AC nominal, 50- 60Hz (switchable), 60VA maximum
<b>Fuse Rating</b>	AC 110 - 120V T1.6AL 250V AC 220 - 240V T800mAL 250V
<b>Additional Features</b>	Energy saving AUTO power function Switchable phase, 0 or 180 degrees Volume and crossover frequency controls
<b>Magnetic Shielding</b>	No
<b>Weight</b>	10.0kg (24.3lbs)
<b>Dimensions (including feet) H x W x D</b>	420mm x 275mm x 370mm (16.5" x 10.8" x 14.6")
<b>Finish</b>	Gloss Black
<b>Supplied Accessories</b>	Country specific mains cable (cord)

Tannoy United Kingdom	T: 00 44 (0) 1236 420199	E: enquiries@tannoy.com
Tannoy Deutschland	T: 00 49 (180) 1111 881	E: anfragen@tannoy.com
Tannoy Middle East	T: 00 971 (04) 4401208	E: enquiries@tannoy.com
TCIGroup International	T: 00 45 8742 7000	E: info@tcgroup-international.com
TCIGroup Americas	T: 00 1 (519) 745 1158	E: info@tcgroup-americas.com

Tannoy adopts a policy of continuous improvement and product specification is subject to change.