



Description

No longer do you need to purchase several large amplifiers to obtain a high performance multizone audio system. The RMB-1512 features an advanced Class D design that provides plenty of power (12 x 100 watts into 8 ohms) for the most demanding multizone audio systems, but never runs the danger of overheating itself or other electronic components placed in the same vicinity. The RMB-1512 features everything needed for remote operation and custom installation including 12 volt trigger signal sensing, input bussing, sum-to-mono, buffered link output, front panel attenuation control, five-way binding posts and screw terminals.

**Note – all Rotel 15 series components may be rack mounted and remotely controlled via RS-232, IR, or 12 volt (depending on model) for complete stealth operation.*

Specifications

Power Output	100 watts x 12ch (20 Hz-20kHz, <0.03% THD, 8 ohms)	Frequency Response (± 1 dB)	10Hz-40kHz (+3dB)
all channels driven	200 watts x 12ch (20 Hz-20kHz, <0.03% THD, 4 ohms)	S/N Ratio (IHF A)	109 dB
IM Distortion	<0.02%	Dimensions (W x H x D) mm	431 x 144 x 407 mm
Damping Factor (8 ohms)	>200	Dimensions (W x H x D) in	3U / 17 x 5 5/8 x 16 in
Input Sens. / Impedance	1.25 V/9.9 k Ohms		

www.rotel.com

The Rotel Co. Ltd.
10-10 Shinsen-Cho
Shibuya-Ku,
Tokyo 150, Japan

Rotel of America
54 Concord St.
N. Reading, MA 01864
USA
T +1 978 664 3820
F +1 978 664 4109

Rotel Europe
Dale Road
Worthing
West Sussex BN11 2BH, UK
T +44 (0) 1903 221 763
F +44 (0) 1903 221 525