

## NEW PRODUCT MS ACTIVE SUBWOOFER ANNOUNCEMENT

Dear Valued Distributor,

Following the success of the MX Series home cinema speakers, Mission is now proud to introduce a range of active subwoofers to complement its full range siblings starting with MS300 and MS400, followed shortly by MS800.

These MS active subwoofers have impressive, newly developed 8-inch (200mm), 10-inch (250mm) and 12-inch (300mm) long throw bass drivers of astounding bass impact. The sealed box design provides fast and intensive bass response while the employment of a custom designed balance drive Class D power amplifier further provides power and speed unheard of in products of comparable price level.



### Features:

1. The low pass filter slope is continuously adjustable from 30Hz to 120Hz.
2. A phase inverter switch eases subwoofer placement.
3. Low level inputs, a dedicated LFE input and high pass output connections are provided for versatility.
4. Auto power sensor is sensitive enough to detect incoming signals of extremely low level for activation of the subwoofer.

While focused on functionality and a very significant price/quality correlation, the MS active subwoofers will not only well integrate into any interior but also elevate the exceptional performance of your existing setup to an unprecedented level. Listen for yourself and get ready to be stunned!

**T.B.A.**



## Specifications

Model	MS-300 Subwoofer	MS-400 Subwoofer	MS-800 Subwoofer
Description/Format	Active Dynamic-Drive IB subwoofer	Active Dynamic-Drive IB subwoofer	Active Dynamic-Drive IB subwoofer system
Drive Units	1 x (8")200mm cone long-throw	1 x (10")250mm cone long-throw	1 x (12")300mm cone long-throw
Frequency Response	40 - 120Hz $\pm$ 3dB	35 - 120Hz $\pm$ 3dB	30 - 120Hz $\pm$ 3dB
Amplifier Power	150W	215W	400W
Peak Power Output	330W	450W	850W
Line Input Sensitivity	200mV	200mV	200mV
Crossover Range	30 - 120Hz	30 - 120Hz	30 - 120Hz
Inputs	Stereo Line In (2 x	Stereo Line In (2 x	Stereo Line In (2 x
Input Impedance	Line In 10k $\Omega$ LFE 5k $\Omega$	Line In 10k $\Omega$ LFE 5k $\Omega$	Line In 10k $\Omega$ LFE 5k $\Omega$
Signal-to-noise ratio	$\geq$ 85dB	$\geq$ 85dB	$\geq$ 85dB
Avg. Max Output	110dB	115dB	117dB
Features	Phase inversion, Auto on-off, High	Phase inversion, Auto on-off, High	Phase inversion, Auto on-off, High pass line
Dimensions (H x W x	341 x 296 x 325mm	402 x 352 x 375mm	447 x 400 x 425mm
Net Weight	9.4kg	14.6kg	17.2kg
Gross Weight	11.5kg	17kg	20.3kg
Finishes	Black Sandex Vinyl	Black Sandex Vinyl	Black Sandex Vinyl
Accessories	IEC power cord,	IEC power cord,	IEC power cord, Spikes

\* Specifications are subject to change without prior notice.

For more information, contact any of our local Mission sales representatives.

Regards,

IAG, Hi Fi Marketing

6th October 2011